

865Q PRO 150W ULTRA **ETHERNET EXTENSION EXPERTS** POE EXTENDER KIT (



- The PLANET's most trusted and deployed brand since 1982
- PoE Extender for IP Cameras over 9 times further than IEEE 802.3 specs
- Leverage existing wiring including coax model up to 3,000ft (915m)
- Delivers Ultra PoE 4-pair output on pins 3/4/5/6 - positive power on pins 1/2/7/8 - negative power
- ▶ PoE Output 802.3af, at, bt
- Secure and Encrypted Communications between devices
- ENABLE-IT USA Factory Floor Direct Same Day Shipping



The Enable-IT 865Q PRO 150W Ultra PoE **Extender Solution.**

The 865Q PRO enables the simple installation of a high powered PoE devices like Axis Q or other high power IP Cameras, Aruba and Cisco Access points up to 3,000ft (915m) from your LAN and Power Source. This is ideal for installing any PoE IP Security cameras or PoE WiFi Access Points.

Leverage existing or new wiring that is contiguous all the way up to 3,000ft (915m), encrypted and secure, effectively saving you thousands in labor, administration, and security.

Put your PoE device where you need to and not where you are limited to.

HIGHLIGHTS

- Drive 150W PoE Devices at Distance.
- Network equipment independence transparent to LAN protocols
- Professional Business Grade, Solid reliability
- Limited Lifetime Manufacturer Warranty
- Optional 4 year Next Business Day Advanced Replacement for about \$2 per month
- Same Day Discounted Rate Shipping -US West Coast Factory Floor Direct.
- 45-day Money Back Guarantee



FEATURES & SPECIFICATIONS

Features:

- Ultra PoE up to 3,000ft (915m) away. 9x times past the IEEE barrier of 328ft or 100m with PoE+ 56V 150W or power
- Gigabit Ethernet full-duplex service
- Complete plug and play devices
- Ideal for deploying PoE devices where you need saving thousands on install
- Complete kit does not require any additional equipment or converters. Includes an $56V \sim 150W$ DC Injector.
- External LED's for Power and LAN activity.

Specifications:

Ethernet: (1) Gigabit LAN RJ-45 10/100/1000 Base-TX auto sensing port

Interlink: RJ-45 (1-Pair) 865QC PRO - 75 Ohm Coax BNC (1-Pair)

Unit Dimensions:

Height 1" (26mm) Depth 3.25" (82.5mm) Width 4.37" (111mm)

Functionality:

10/100/1000Mbps full-duplex Ethernet Data 1.2Gbps Interconnect throughput Ethernet LAN Protocol Independent Ethernet LAN MTU 1500 - Max 2000 IP VLAN pass though

Environment:

Operating Temp: -49°F to 168°F (-45°to 76°C) Humidity 5% to 95%, non-condensing

