

## Enable-IT 865 LRE & PoE Solution









865 - ETHERNET & POE EXTENDERS



#### **FEATURES & SPECIFICATIONS**

# Voice

- Video
- Data
- PoE

Extends Full-Duplex 100MB Ethernet up to 2,500'/762m to a self powered (PoE) CPE unit and up to 1,500'/458m to a PoE WiFi AP, IP Camera or PoE Device

Small footprint and standard RJ-45 interfaces for simple installation

Saves costs of re-wiring and expensive LAN equipment

Plug and Play installation allows rapid connectivity of your extended network

Made in the USA

The Enable-IT 865 Ethernet and PoE Extender kit is the world's only available solution to deliver Voice, Data and PoE in a combined package that exceeds the IEEE distance limitations for all Ethernet equipment and 802.3af PoE. The 865 enables the simple installation of a PoE device up to 1,500ft (458m) From your LAN and Power Source. — This is ideal for installing PoE IP Security cameras or PoE WiFi Access Points or for a standalone remote self powered LAN up to 2,500ft (762m).

#### **HIGHLIGHTS**

- Extends Ethernet LAN cabling 7.7 times the IEEE restrictions to self powered units via PoE
- Can drive your Remote PoE device and LAN data up to 1,500ft/458m – ideal for PoE IP Cameras and PoE WiFi Access Points
- Broadband Transport for delivering Voice, Data, Video over any CAT rated or telephone cabling
- Can be used on all LAN devices including switches, routers, hubs, gateways and end nodes
- Rapid and Easy Installation using RJ-45 LAN interfaces and cabling

#### Features:

- Extends standard Ethernet Networks 6 times beyond the 328ft or 100m limitation of twisted pair Ethernet
- Includes 48v PoE Injector to power remote unit at 2,000' or power a second PoE device up to 1,000'
- Supports digital VoD channels
- 100 Mbps full-duplex service
- Single RJ-45 port for PoE & LAN
- Single RJ-11 POTS port (telephone)
- MPEG over IP support

### Specifications:

LAN interface: Dual RJ-45 100Mbps One with PoE support

## **Dimensions:**

Height: 1.5" (38mm) Length: 5.75" (146mm) Width: 3.75" (95mm)

#### **Functionality:**

Up to 700ft(200m) - 100Mbps 700ft(200m) to 1,350ft(400m) - 90Mbps 1,350ft(400m) to 2,000ft(610m) - 75Mbps

Max Distance 2,500ft/762m standalone 1,500ft/458m PoE device

Interfaces

865 Units – (3) RJ-45 ports 100Mbps Ethernet w PoE 865 Interlink port

(1) RJ-11 Dual line POTS

#### **Environment**

Temperatures
Operating Temp:
 -20° to 70°C/-4° to 160°F
Storage Temp:
 25° to 70°C/-13° to 160°F
Humidity
 5% to 95%, non-condensing

